

DECLARATION OF PERFORMANCE

EN 13984:2013

Boulder Business Park, Pioneer Way, Lincoln LN6 0QR

Flexible sheets for waterproofing. Plastic and rubber vapour control layers.

Identification : SF19PLUS-BD-CPR-01-04-19

Reaction to Fire : Class F

Notified Body : BTTG, KIWA

Water Penetration : W1



1. Product Type

Unique identification code of the product type:

SuperFOIL SF19+ Multi Foil Insulation

2. Type:

Type batch or serial number or any other element allowing identification of the construction product as required under article 11(4): See product or packaging

3. Intended Use:

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Flexible sheets for waterproofing; plastic and rubber vapour control layers

4. Name, registered trade name:

Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Boulder Developments Ltd,Boulder Business Park, Pioneer Way, Lincoln, LN6 0QR

5. Contact Address:

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): Not Applicable (refer to section 4)

6. AVCP:

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, annex V: System 3

7. Notified Body:

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, annex V: hEN13984

Notified Body	Reg. Number	Test	Result	Date of Issue
BTTG	0338	Reaction to Fire	Class F	28/03/2022
KIWA	1640	Water Penetration	W1	07/12/2023

Performed type testing under system 3 and issued test reports

8. Notified Body (ETA):

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: Not Applicable (see 7)

Document Number:SF-TE-FO-056	Submitted By:Gavin Phillips	Review Date:12/11/2026
Issue Date:12/11/2024	Approved By:Gavin Phillips	Revision Number:1

DECLARATION OF PERFORMANCE

EN 13984:2013

Boulder Business Park, Pioneer Way, Lincoln LN6 0QR

Flexible sheets for waterproofing. Plastic and rubber vapour control layers.

Identification : **SF19PLUS-BD-CPR-01-04-19**Reaction to Fire : **Class F**Notified Body : **BTTG, KIWA**Water Penetration : **W1**

9. Additional Information:

Essential Characteristics	Performance	CE Standard
Emittance	0.05	NEN EN 16012 : 2012
Thickness	45mm	NPD
Tensile Properties - Length *	606 / 580N /50mm	EN 12311-1:2000
Tensile Properties - Width *	514 / 526N/50mm	EN 12311-1:2000
Elongation - Length *	24%	EN 12311-1:2000
Elongation - Width *	23%	EN 12311-1:2000
Resistance to Tearing - Length	275N	EN 12310-1:2000
Resistance to Tearing - Width	305N	EN 12310-1:2000
Flexibility at low temp - (pliability)	-40°C	EN 1109:2013
Resistance to Water Penetration	W1	EN 1928:1999
Water Vapour Transmission	2050 MNs/g / 410sd	EN 1931:2001
Reaction to Fire	Class F	EN 13501-1:2018

10. Hazardous Substances: None

11. Properties Excluding the CE Mark: None

12. Declaration:

The performance of the product identified in **points 1 and 2** is in conformity with the declared performance in **point 9**.
This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in **point 4**.

Signed for and on behalf of the manufacturer by:

Craig Bown, Director of Boulder Developments Ltd
28-03-2024

Document Number:SF-TE-FO-056	Submitted By:Gavin Phillips	Review Date:12/11/2026
Issue Date:12/11/2024	Approved By:Gavin Phillips	Revision Number:1