

DECLARATION OF PERFORMANCE

EN 13984:2013

Boulder Business Park, Pioneer Way, Lincoln LN6 OQR

Flexible sheets for waterproofing. Plastic and rubber vapour control layers.

Identification: SF40-BD-CPR-01-04-19

Reaction to Fire : Class E

Notified Body: BTTG, KIWA

Water Penetration: W1



1. Product Type

Unique identification code of the product type:

SuperFOIL SF40 Multi Foil Insulation

2. Type:

Type batch or serial number or any other element allowing identification of the construction product as required under article 11(4): **See product or packaging**

3. Intended Use:

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Flexible sheets for waterproofing; plastic and rubber vapour control layers

4. Name, registered trade name:

Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Boulder Developments Ltd, Boulder Business Park, Pioneer Way, Lincoln, LN6 OQR

5. Contact Address:

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not Applicable (refer to section 4)**

6. AVCP:

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, annex V: **System 3**

7. Notified Body:

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, annex V: **hEN13984**


Notified Body	Reg. Number	Test	Result	Date of Issue
BTTG	0338	Reaction to Fire	Class E	09/05/2022
KIWA	1640	Water Penetration	W1	07/12/2023

8. Notified Body (ETA):

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **Not Applicable (see 7)**

Document Number: SF-TE-FO-064	Submitted By:Gavin Phillips	Review Date: 23/01/2027
Issue Date:23/01/2025	Approved By: Gavin Phillips	Revision Number:1





DECLARATION OF PERFORMANCE

EN 13984:2013

Boulder Business Park, Pioneer Way, Lincoln LN6 0QR

Flexible sheets for waterproofing. Plastic and rubber vapour control layers.

Identification: SF40-BD-CPR-01-04-19

Reaction to Fire : Class E

Notified Body: BTTG, KIWA

Water Penetration: W1



9. Additional Information:

Essential Characteristics	Performance	CE Standard
Tensile Properties - Length *	698/509N /50mm	EN 12311-1:2000
Tensile Properties - Width *	595/432N/50mm	EN 12311-1:2000
Elongation - Length *	22%/24%	EN 12311-1:2000
Elongation - Width *	19%/26%	EN 12311-1:2000
Resistance to Tearing - Length	685N	EN 12310-1:2000
Resistance to Tearing - Width	585N	EN 12310-1:2000
Water Vapour Transmission	2462 MNs/g	EN 1931:2001
Resistance to Water Penetration	W1	EN 1928:2000
Reaction to Fire	Class E	EN 13501-1:2018
Joint Strength	NPD	EN 12317-2:2010
Resistance to impact	NPD	EN 12691 :2018
Additional Information	Performance	CE Standard
Flexibility at low temp - (pliability)	-40°C	EN 1109:2013

10. Hazardous Substances: None

11. Properties Excluding the CE Mark: None

12. Declaration:

The performance of the product identified in **points 1 and 2** is in conformity with the declared performance in **point 9**.

This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Craig Bown, Director of Boulder Developments Ltd

28-03-2024



Document Number: SF-TE-FO-064	Submitted By:Gavin Phillips	Review Date: 23/01/2027
Issue Date:23/01/2025	Approved By: Gavin Phillips	Revision Number:1

