SuperFOIL®

DECLARATION OF PERFORMANCE

EN 13859-2:2014

Boulder Business Park, Pioneer Way, Lincoln LN6 3DH

Underlays for discontinuous roofing.
Underlays for walls.

Identification : **SFBB-BD-CPR-01-04-19**

Reaction to Fire : **Class F**

Notified Body : **KIWA**

Water Penetration : **W1**

CE 15

Product Type

Unique identification code of the product type:

SuperFOIL SFBB Thermal Breathable Membrane

1. Unique Identification code of product type:

Type batch or serial number or any other element allowing identification of the construction product as required under article 11(4): **Type and batch numbers are printed on each product and packaging label**

2. Intended Use:

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Underlays for discontinuous roofing.
Underlays for walls.

3. Name, registered trade name:

Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Boulder Developments Ltd,Boulder Business Park, Pioneer Way, Lincoln, LN6 3DH

4. Contact Address:

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not Applicable (refer to section 3)**

5. AVCP:

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, annex V: **System 3**

6a. Notified Body:

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, annex V: **hEN13859**

Notified Body	Reg. Number	Test	Result	Date of Issue
KIWA	1640	Reaction to Fire	Class F	25/02/2022
KIWA	1640	Water Penetration	W1	07/02/2023

Performed type testing under system 3 and issued test reports

6b. Notified Body (ETA):

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **Not Applicable (see 6a)**

Document Number: SF-TE-FO-069	Submitted By: Gavin Phillips	Review Date: 23/01/2027
Issue Date: 02/10/2025	Approved By: Gavin Phillips	Revision Number: 3

SuperFOIL®

DECLARATION OF PERFORMANCE

EN 13859-2:2014

Boulder Business Park, Pioneer Way, Lincoln LN6 3DH

Underlays for discontinuous roofing.
Underlays for walls.

Identification : **SFBB-BD-CPR-01-04-19**

Reaction to Fire : **Class F**

Notified Body : **KIWA**

Water Penetration : **W1**

CE 15

7. Declared Performance:

Essential Characteristics	Performance	CE Standard
Tensile Properties - Length *	135 / 13 N/50mm	EN 12311-1:2000
Tensile Properties - Width *	85 / 20 N/50mm	EN 12311-1:2000
Resistance to Tearing - Length	110N	EN 12310-1:2000
Resistance to Tearing - Width	120N	EN 12310-1:2000
Water Vapour Transmission	0.153 MNs/g	EN ISO 12572:2016A1+2024
Flexibility at low temp - (pliability)	-40°C	EN 1109:2013
Resistance to Water Penetration	W1	EN 1928:2000
Reaction to Fire	Class F	EN 13501-1:2018
Resistance to Air Penetration	NPD	EN12114:2000

8. Declaration:

The performance of the product identified above is in conformity with the set of declared performance/s.
This Declaration of Performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above:

Signed for and on behalf of the manufacturer by:

Name: Craig Bown, Director of Boulder Developments Ltd

At: Boulder Developments Ltd, Boulder Business Park, Pioneer Way, Lincoln, LN6 3DH

Date of issue: 28-03-2024

Signature:

