



ADDITIONAL DETAILS

SFBB BREATHABLE MEMBRANE

2-IN-1 BREATHABLE MEMBRANE AND RADIANT BARRIER


W1 WATERTIGHT BREATHABLE MEMBRANE PREVENTS CONDENSATION ISSUES

ACTS AS RADIANT BARRIER, ENHANCING THERMAL PERFORMANCE

HIGHLY DURABLE MATERIAL FOR LONG-LASTING PERFORMANCE

Ideal For New Build & Retrofit

CUT TO SIZE STAPLE TO SURFACE SEAL WITH TAPE



SuperFOIL SFBB is a breathable membrane designed to help prevent the formation of mould and damp by reducing the risk of condensation and by keeping water out of your build-up thanks to its W1 watertightness.

The continuous nature of SuperFOIL SFBB makes it an ideal product to provide comprehensive protection; and its reflective barrier properties provide a boost to the thermal performance.



SF6210
5060355996412



Batch No:

Suitable For Roof, Wall and Floor Applications :

- Re-Roofing
- New Build & Retrofit
- Conversions & Extensions
- Boats, Caravans & Campervans

Width: 1.5m

Length: 25m

Coverage: 37.5m²

<p>EN 13859-2:2014 Underlays for discontinuous roofing. Underlays for walls. DOP REF: SFBB-BD-CPR-01-04-19 https://www.superfoil.co.uk/products/radiant-barriers/sfbb</p>	<p>ID Notified Bodies: 1640</p> <p>Reaction to Fire - Class F Water penetration - W1 Tensile Properties (Length) - 135 / 13 N/50mm Tensile Properties (Width) - 85 / 20 N/50mm Elongation (Length) - 70% / 3%</p>	<p>Elongation (Width) - 60% / 5% Resistance to Tearing (Length) - 110N Resistance to Tearing (Width) - 120N Water Vapour Transmission - Pass</p>
--	---	--

SuperFOIL SFBB 1.5M x 25M

Performance

Roof Performance (R Value)	0.29
Wall Performance (R Value)	0.36
Emittance	0.19
Resistance to Water Penetration	W1
Reaction to Fire (Euroclass)	Class F

Product Dimensions

Thickness	<1mm
Length	25m
Width	1.5m
Coverage	37.5m ²
Weight	5.4kg

Installing SuperFOIL Multipurpose Wrap is as easy as 1, 2, 3.



Measure the project area, then cut the insulation to the measured size using heavy-duty scissors or a utility knife.



Secure the product to the surface with a staple gun. When installing to hard surfaces, use timber battens.



Seal any joints / overlaps with an appropriate foil tape to enhance your airtight finish.

If you want to make sure you're getting the most from your SuperFOIL, you should make sure to...

- Include an air gap on either side of the product (where possible);
- Use the the right size of battens and staples;
- Follow any installation guidance provided by SuperFOIL;

⊕ Sustainability Pledge

SuperFOIL is a carbon-neutral business dedicated to making a positive impact, both on the environment and in people's lives, by prioritising sustainability at every level of our business: from production to installation.



Recommended Products

We recommend the following products to ensure the very best installation possible:



SuperFOIL®
Breather Tape
75mm x 25m



SuperFOIL®
XL Scissors
12 Inch



SuperFOIL®
3-in-1 Staple Gun
1000x10mm

SuperFOIL®

CHANGE THE WAY YOU INSULATE

With over two decades of industry experience, our experts are always ready to help you get the most out of our products. If you have any questions or require technical advice please get in touch on **01636 639900** Monday to Friday 9am-5pm.